

CHLORIDE

Secure Power Always

Linear Plus and Linear Plus RM 6 kVA and 10 kVA



Uninterruptible Power Supply

Linear Plus and Linear Plus RM 6 kVA and 10 kVA

Chloride's Linear Plus family is available in 6 kVA and 10 kVA single-phase output tower and rack units. Linear Plus 10 kVA 1/1 & 3/1 tower units are single-phase output and single- or three-phase input, obtainable via auto selection.

Incorporating modern double conversion technology, attractive design and multiple system integration capabilities, the Linear Plus family offers the most efficient all-round protection against all types of disturbances and problems in the mains supply system.

Leading Technology

Linear Plus uses double conversion technology to provide a secure power architecture for your mission critical applications. This option ensures the highest level of voltage and frequency regulation and may be the only practical alternative for environments where the quality of the mains electricity is low.

Reliability

Linear Plus can provide the security of a truly redundant parallel system, offering the highest degree of reliability for mission critical loads and applications. User replaceable batteries allow the simple swap out of batteries without interruption to the secured system.

Flexibility

The optional additional battery charger means Linear Plus delivers extended autonomies making the UPS ideal for industrial applications and those environments with a requirement for longer run times.

Communication

The front panel features an attractive seven language LCD display which communicates the latest information on the UPS operating status, facilitating UPS control and monitoring. Linear Plus is fully compatible with Chloride's Connectivity suite facilitating power management for IT and network managers.

Monitoring

The Linear Plus family is fully compatible with LIFE.net, Chloride's remote monitoring tool. LIFE.net is the nearest thing to having a Chloride engineer permanently onsite and provides:

- Continuous real-time UPS monitoring
- Automatic transmission of daily status reports
- Real-time diagnosis of all UPS operating parameters
- Remote fix capability
- Monthly UPS operational status reports
- Unique ETS function for trouble shooting the most common operating anomalies
- Power quality monitoring to effectively manage power disturbance trends.

Applications

- Network & VoIP Protection/departmental information systems in decentralised environments
- Medical Equipment - IT Systems, diagnostic equipment, clinical laboratories and monitoring support systems
- Industrial environments such as process control equipment
- LAN / WAN Servers & IT rooms
- Emergency lighting
- Bank branches.

Secure Power Always

Supplying you with a UPS alone will never deliver the level of business continuity

you require. Chloride offers a range of maintenance plans which will:

- Help deliver reliability to your load
- Extend the life of your power protection equipment
- Optimise your capital expenditure
- Provide risk management at a fixed cost
- Help to control your business environment
- Generate a proactive approach to disaster recovery.

Contact your local Chloride sales office for more information.

Delegate your power management to the experts.

Linear Plus	6/11	10/11	10/31
INPUT			
Number of phases	1	1	3+N
Voltage (V)	230	230	380/400
Tolerance (V)	176-276	176-276	304-478
Frequency (Hz)	50/60		
Power factor	0.97	0.97	0.95
OUTPUT			
Number of phases	1		
Voltage (V)	220/230/240		
Frequency (Hz)	50/60		
Power factor	0.7		
Static output voltage stability % due to 100% load variation	±2		
Output harmonic distortion	IEC/EN 62040 - 3 Compliant		
GENERAL			
Operating temperature (°C)	0 - 40		
Colour	RAL 7016		
Max. noise levels at 1 metre (dBA)	<50		
AC/AC efficiency (%)	92		
Standard communication interfaces	1 x RS 232		
Dimensions			
Height (mm)	800	800	800
Width (mm)	300	300	300
Depth (mm)	675	675	675
UPS weight (kg) (without batt.)	51	54	54
UPS weight (kg) (with internal batt.)	107	110	110

Linear Plus RM	6/11	10/11
INPUT		
Number of phases	1	1
Voltage (V)	220/230/240	220/230/240
Tolerance (V)	176-276	176-276
Frequency (Hz)	50/60	50/60
Power factor	>0.97	>0.97
OUTPUT		
Number of phases	1	1
Voltage (V)	230	230
Frequency (Hz)	50/60	50/60
Power factor	0.7	0.7
Static output voltage stability % due to 100% load variation	±2	±2
Output harmonic distortion	EN 62040 - 3 Compliant	
GENERAL		
Operating temperature (°C)	0 - 40	0 - 40
Colour	RAL 7016	RAL 7016
Max. noise levels at 1 metre (dBA)	< 50	< 50
AC/AC efficiency (%)	92	92
Standard communication interfaces	1 x RS 232	1 x RS 232
Dimensions		
Height (HU)	3U	3U
Width	19"	19"
Depth (mm)	720	720
UPS weight (kg)	24.5	27

This publication is issued to provide online information only and is not deemed to form any part of any offer and/or contract. The company has a policy of continuous product development and improvement, and we therefore reserve the right to vary any information without prior notice. MK44L0UKLINP Rev. 3-11/2007

**Chloride UPS Systems HQ
WORLD HEADQUARTERS**

Via Fornace 30
40023 Castel Guelfo (BO)
Italy

T +39 0542 632 111
F +39 0542 632 120
E enquiries@chloridepower.com

CHLORIDE

www.chloridepower.com

Closest Chloride Contact in Australia:
Chloride Power Protection
Ground Floor
16 Giffnock St, North Ryde
NSW 2113
Australia

T +61 2 9888 1266
F +61 2 9888 1966
E australia.sales@chloridepower.com

www.chloridepower.com/au

Closest Chloride Contact in UK:
Chloride Power Protection
George Curl Way
Southampton, Hampshire
SO18 2RY
United Kingdom

T +44 (0) 23 8061 0311
F +44 (0) 23 8061 0852
E uk.enquiries@chloridepower.com

www.chloridepower.co.uk

Closest Chloride Contact in UAE:
Chloride UPS Systems Middle East
Building 5, Office 104
Dubai Internet City - Dubai
UAE
PO Box 72536

T +971 4 391 3205
F +971 4 391 6803
E middleeast.sales@chloridepower.com

www.chloridepower.com/middle-east

Closest Chloride Contact in USA:
Chloride Power Protection
27944 North Bradley Road
Libertyville
IL 60048
USA

T +1 800 239 2257
F +1 800 833 6829
E usa.info@chloridepower.com

www.chloridepower.com/us

For a full list of contacts please visit our website at www.chloridepower.com



Certificate No. EMS 76732 Certificate No. FM 11043